

Symmetrix 3330-18

Open Systems and Mainframe Specifications

Sample Configuration Data

Physical Disks	Open Systems Raw Capacity (GB)*	Mirrored Capacity (GB)*		RAID-S Capacity (GB)*		SRDF Capacity (GB)*		Maximum Cache (MB)**
		Open	Mainframe	Open	Mainframe	Open	Mainframe	
4	72	36	35	54	53	72	71	8,192
8	144	72	71	108	107	144	143	8,192
12	217	108	107	162	161	217	214	8,192
16	289	144	143	217	214	289	286	8,192
24	434	217	214	325	322	434	429	8,192
32	579	289	286	434	429	579	572	8,192

Note: Hyper-Volume Extension can increase the number of logical volumes to 1,024 maximum.

*All capacities are based on 1GB=1,000,000,000 bytes. For AS/400 capacities, contact your EMC sales representative.

**Individual model cache capacities are based upon specific configurations and customer requirements.

Host Connectivity

All Models	Open Systems		Mainframe	
	Min	Max	Min	Max
Fibre Channel	4	8	–	–
Ultra SCSI	8	16	–	–
FWD SCSI	8	16	–	–
ESCON®*	–	–	4	16

Note: Mixed ESCON, FWD SCSI, Ultra SCSI, and Fibre Channel interfaces are supported.

*ESP-3300 software is required to run ESCON channels.

Disk Emulation

	FBA	3380K	3390-1	3390-2	3390-3	3390-9
MB/Volume	15,979*	1,891	946	1,892	2,838	8,514
Bytes/Track	32,768	47,476	56,664	56,664	56,664	56,664
Bytes/Cylinder	491,520	712,140	849,960	849,960	849,960	849,960
Cylinders/Volume	32,510*	2,655	1,113	2,226	3,339	10,017

*Values represent maximum figures for each configuration.

Hyper-Volume Extension (HVE)

Emulation Mode*	Open Systems		Mainframe				
	2GB**	4GB**	3380K**	3390-1**	3390-2**	3390-3**	3390-9**
Maximum Complete Logical Volumes	8	4	9	18	9	6	2

Hyper-Volume Extension provides the ability to configure a single physical disk device as multiple logical volumes in logical-to-physical relationships ranging from 1:1 to 32:1.

*A single physical disk device can support multiple model types within a single data format emulation mode.

**This emulation mode provides additional space on the physical disk device for use as either a lower than full capacity logical volume for the specified emulation mode, or as a different, smaller model type within the same emulation mode.

Available Software

Model Number	Description
ESP-3300	ESP Enabler software license
FDRSOS	Fast Dump/Restore, Safeguard Open Systems software license*
INFOMOVE-3300	EMC InfoMover Software License
OSYMGR-BAS**	Symmetrix Manager for Open Systems, Base Component software license
OSYMGR-CTL**	Symmetrix Manager for Open Systems, Control Option software license (requires OSYMGR-BAS)
OSYMGR-DDR**	Symmetrix Manager for Open Systems, DDR Option (requires OSYMGR-BAS)
SDM-3300	Symmetrix Data Migration Services software license
SMTF-3300	Symmetrix Multihost Transfer Facility software license
SRDF-3300	Symmetrix Remote Data Facility software license
SRDF-3000 FP	Symmetrix Remote Data Facility FarPoint software license (requires SRDF-3300)
SRDF-HC	SRDF Host Component software license
SYMMGR	Symmetrix Manager Base Component software license
TimeFinder-3000	EMC TimeFinder software license

*See an Innovation Data Processing sales representative for additional information.

**Also available with Windows NT graphical user interface (GUI).

EMC²

The Enterprise Storage Company

EMC Corporation
Hopkinton
Massachusetts
01748-9103

1-508-435-1000

In North America
1-800-424-3622 ext. 362

www.EMC.com



Multihost Support

Vendor	System	Minimum Operating System
Bull®	Escala Series M, D, R, E, T, RT, Escala Series, RL, RL470	AIX 4.2.1, AIX 4.3
DEC®	AlphaStation and AlphaServer Series 3000 AXP, Models: 300-900, 1000, 2000, 2100, 4000/4100, 8200, & 8400	Digital® UNIX® V3.2A, OpenVMS® V6.2, Windows NT® V3.5.1
Data General®	Avion® 5500 (88K-based), 4900/5000 (Intel-based)	DG/UX® R4.11 MU03
Data General	AV4900, AV5900 (Pentium®)	Windows NT V4.0
HP®	3000/900 Series	MPE/ix 5.0
HP	9000/700 Series: 725/100, 735/99, 735/125, 755/99, 755/125, 715/100XC, B-Series, C-Series, J-200, J-210, J-210CX, J-250	HP-UX® 9.05, 10.01
HP	9000/800 Series: E, F, G, H, I, T500, D-Class, K-Class, T600 TFC	HP-UX 9.04, 10.01, 10.20 TFC
HP	9000 K-Class, T600, D-Class, V-Class (V2200, V2250)	HP-UX 9.04, HP-UX 10.01, HP-UX 11.0
IBM®	AS/400® (all 9406 including RISC, except Model B)	OS/400® V2R3
IBM	RS/6000™	AIX® 3.2.5
IBM	SP®	AIX 4.2.1
IBM	S/390® & S/370™	Any
ICL	SmartController SDS	Open VME 2
Intel®-Based Servers	All	Novell® 3.12, OS/2® 2.1, Windows NT 3.5
NCR®	34xx, 35xx, 41xx, 45xx, 3600AP, 5100 (S, C, M), 4300, 4700, 5150	UNIX SVR4 2.03.01 & 3.01, Windows NT 4.0
Pyramid	Nile Series	Data Center OSx 94D070.6
Sequent®	Symmetry® 2000 & 5000, NUMA-Q	DYNIX/ptx® 2.1.5, 4.3.0
Siemens-Nixdorf®	RM 400/600, RM 400C/600E	SINIX® V5.42, Reliant UNIX V5.43C10
Siemens-Nixdorf	400C/600E	Reliant UNIX V5.43C10
Siemens-Pyramid®	Nile® Series, RM1000	DataCenter® OSx 94D079.6, 95M079
Silicon Graphics®	Challenge® S, L, DM, & XL	IRIX® 5.3
Silicon Graphics	Origin 200 and 2000	IRIX 6.4.1
Sun®	SPARCserver® and SPARCcenter 10, 20, 1000, 2000	SunOS® 4.1.3, Solaris® 2.3
Sun	UltraSPARC PCI-based, Ultra, Netra, & UltraEnterprise Workstations and Servers	Solaris 2.5, Solaris 2.6
Unisys®	SMP61000, U6000/XXX, AQUANTA Series Servers	UNIX SVR4 1.4 & 1.3.1, Windows NT V4.0,

Note: Contact your local EMC sales representative for specific hardware and software configuration support.

Physical Specifications*

Model Series	Height ** (in/cm)	Width (in/cm)	Depth (in/cm)	Front Service Area (in/cm)	Rear Service Area (in/cm)
3330	46.0/116.9	21.0/53.3	36.0/91.5	36.0/91.5	36.0/91.5

**An additional 18 inches (45.7cm) is required for ceiling clearance.

Weight*

Physical Volumes	4	8	12	16	24	32
Weight (lb/kg)	571/259	583/265	595/270	607/276	631/286	655/297

Power and Cooling Data*

Physical Volumes	4	8	12	16	24	32
Power Consumption (kVA)	0.848	0.951	1.053	1.155	1.359	1.547
Heat Dissipation (Btu/hr)	2,809	3,147	3,485	3,823	4,498	5,174

Power Specifications

	North America	International
Input Voltage (VAC)	208	Country Specific
Frequency (Hz)	60, single phase	Country Specific
Circuit Breaker (Amps), max.	20	Country Specific
User Connector	(2) Russellstoll® 3913 flex or (2) Russellstoll 3743 rigid	Country Specific
Power Connector	Russellstoll 3720	Country Specific
Auto-Call Modem Requirements	The Auto-Call modem requires connection to a 110VAC power source at 60Hz through a NEMA 5-15R receptacle. International installations are country specific.	

Note: Symmetrix 3330-18 now comes with two power connectors.

Environmental Specifications (operating)

Temperature (°F/°C)	59–90°F/15–32°C
Altitude (ft/m), max.	8,000/2,500
Humidity (%), non-condensing	10–80/5–99 (non-operating)
Raised Floor	Recommended

*Values represent maximum figures for each configuration.



http://www.raid-advisory.com/emc.html



The information presented here is summary in nature, subject to change, and intended for general information only. Additional details and specifications concerning the operation and use of EMC equipment and software are available in the applicable technical literature.

EMC and Symmetrix are registered trademarks and EMC, TimeFinder, DataReach, PowerPath, The Enterprise Storage Company, EMC Enterprise Storage, and SRDF are trademarks of EMC Corporation. Other trademarks are the property of their respective owners. RAB is a Certification Mark of the RAID Advisory Board, St. Peter, MN, 507-931-0967.

© 1999 EMC Corporation. All rights reserved. Printed in the USA. 2/99

Specification Sheet
C717.2